

PRODUCT DATA SHEET

STONE TYPE WELSH BLUE PENNANT SANDSTONE

PRODUCT RIVEN PAVING (Flagstones)

DESCRIPTION

Appearance: Fine grained pennant sandstone
Predominantly blue grey in colour with some brown tones.

Finish: Riven – Hand split flagstones

Geological Type: From the Rhondda Beds of the Pennant series of Carboniferous Sandstones

Quarry of Origin: Gwrhyd Quarry



APPLICATION

Commercial, Public area's and high status residential landscaping projects. Our Premium Paving 45mm<65mm thickness is ample for class 6 use (HGV on regular basis) Some Local Authorities specify our Commercial Paving with greater thickness, which we can accommodate up to 90mm thick.

SUPPLY

Pack Weight	Approximately 1300 < 1500 Kgs.
Packaging	Wooden Pallets

PHYSICAL PROPERTIES

Work Dimensions	Hand split riven paving with sawn edges to 4 sides x random lengths 200mm < 900mm x 40mm < 60mm thickness
Widths	Standard widths 300mm, 400mm, 450mm, 500mm, other widths are available, please contact the office for details.
Coverage	Paving is sold per square metre
Compressive strength	122 MPa min
Water Absorption	0.74%

FUTHER INFORMATION

WEATHERING

It should be appreciated that with all products weathering and site conditions can cause shade variation to appear on individual units. This does not in any way affect the performance of the units and any such variation will diminish over a period of time as the product matures.

NOTE: As with all natural stone products the product is subject to colour variation.

GENERAL

Paving is sold in random lengths and due to its hand split nature there is a tolerance in the thickness. Surface texture will have no greater than 5mm undulation.

CONTACT US

For sales and technical information contact Gwrhyd Specialist Stone Sales Office

Gwrhyd@specialiststone.com

Tel. 01639 830650 Fax. 01639 830930